



Driver: \_\_\_\_\_ Class: \_\_\_\_\_

Track: \_\_\_\_\_ Surface: Smooth  Bumpy

Event: \_\_\_\_\_ Traction: High  Low

### Tires

	Brand/Name	Compound	Insert
RF			
LF			
RR			
LR			

Cleaned With: \_\_\_\_\_

Traction Additive: \_\_\_\_\_

Notes: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

### Shocks

	Body Length	Shaft Length	Spring	Oil	Piston	Shock Length	Collar	Spring Cup
RF	S M L	S M L			S M L			Std. Ext.
LF	S M L	S M L			S M L			Std. Ext.
RR	S M L	S M L			S M L			Std. Ext.
LR	S M L	S M L			S M L			Std. Ext.

Shock Notes: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

### Ride Height

LF	RF
LR	RR

### Max Chassis Height

LF	RF
LR	RR

### Corner Weights


LF	RF
LR	RR

Front %	
Rear %	

Measured From:  Bottom of Chassis  Top of Chassis

Total Weight: \_\_\_\_\_  Measured without body

### Rear Suspension



#### Left

- 0
- 1  2
- 3  4
- None
- .060
- .125
- Short
- Long
- Upper
- Lower

#### Camber

- Spacers Behind Hub
- Suspension Mount Shims
- Suspension Mount
- Hub Pin Location

#### Right

- 0
- 1  2
- 3  4
- None
- .060
- .125
- Short
- Long
- Upper
- Lower

#### Left

- Inner
- Outer
- None
- 1.5°
- 3°
- Inner
- Outer

#### Toe

- Outer Link Location
- Anti-Squat
- Bottom Shock Hole
- Hex Offset

#### Right

- Inner
- Outer
- None
- 1.5°
- 3°
- Inner
- Outer

#### Outdrives / Diff.

- Steel
- Alum
- Gear

Gear Diff Fluid: \_\_\_\_\_

Wheelie Bar Height: \_\_\_\_\_

Wheel:  Yes  No

### Aerodynamics

Body: \_\_\_\_\_

Body Mount: Floating (FBM)  Solid

FBM Mount Links – Exposed Turnbuckle F- \_\_\_\_\_ R- \_\_\_\_\_

Rear Deck Height From Bottom Of Chassis: \_\_\_\_\_

Spoiler: \_\_\_\_\_

Spoiler Angle: \_\_\_\_\_ Wickerbill: \_\_\_\_\_

### Power

Motor: \_\_\_\_\_ Speed Control: \_\_\_\_\_

2 Pole  4 Pole  Timing/Boost: \_\_\_\_\_

Endbell Timing: \_\_\_\_\_ Battery: \_\_\_\_\_

Pinion: \_\_\_\_\_ Spur: \_\_\_\_\_ Battery Position: \_\_\_\_\_

Transmitter: \_\_\_\_\_

### Notes:

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_